



SENSING INNOVATION

Top notch **Sensor Solutions**
by Sensinova

www.sensinova.in

TRUE PRESENCE SENSOR

NANO PRO-S

(Surface Mount - 360° Detection)



Hold Time: 5sec-30min
Load Capacity: 800W LED
Detection Range: Movement: 3-4m
 Slight motion: 3-4m
 Breathing: 2-3m
IP Rating: IP20



MICROWAVE SENSOR



NANO 16

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-12min
Load Capacity: 6Amp
Detection Distance: 2-16m (Radius) Adj
IP Rating: IP20



NOVA 4T

(Wall / Ceiling Mounted - 180°/360° Detection)

Hold Time: 10sec-12min
Load Capacity: 5Amp
Detection Distance: Wall: 5-15m Adj,
 Ceiling: 1-8m (Radius) Adj
IP Rating: IP20



NOVA MINI

(Wall/Ceiling Mounted - 180°/360° Detection)

Hold Time: 5sec-30min
Load Capacity: 200W LED
Detection Distance: 5-12m (Radius) Adj
IP Rating: IP20

Manual Override / Bypass



NANO F16

(Flush Mounted - 360° Detection)

Hold Time: 10sec-12min
Load Capacity: 5Amp
Detection Distance: 1-8m (Radius) Adj
IP Rating: IP20



NANO W12

(Wall Mounted - 180° Detection)

Hold Time: 10sec-12min
Load Capacity: 5Amp
Detection Distance: 5-12m (Adjustable)
IP Rating: IP65



NANO HB20

(Highbay Sensor - 360° Detection with 1-10v Dimming)

Hold Time: 5sec-30min
Load Capacity: 5Amp
Detection Distance: 4-10m (Radius) Adj
IP Rating: IP65



NOVA DC NONC

(Ceiling Mounted - 360° Detection)

Input: 12-24V / DC
Hold Time: 8sec-12min
Load Capacity: 5Amp
Detection Distance: 2-8m (Adjustable)
IP Rating: IP20

Dry Contact Output



NOVA PFC-S

(Ceiling Mounted - 360° Detection)

Input: 220-240V / AC
Hold Time: 8sec-12min
Load Capacity: 7Amp (Dry Contact)
Detection Distance: 8m Max (Adjustable)
IP Rating: IP20

Dry Contact Output

DC SENSORS



IRIS S8

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-7min
Load Capacity: 200W LED
Detection Distance: 8m Max (<24°C)
IP Rating: IP20



IRIS F8

(Flush Mounted - 360° Detection)

Hold Time: 10sec-12min
Load Capacity: 200W LED
Detection Distance: 8m Max (<24°C)
IP Rating: IP20



IRIS S12

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-7min
Load Capacity: 5Amp
Detection Distance: 12m Max (<24°C)
IP Rating: IP20



IRIS S12W

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-12min
Load Capacity: 5Amp
Detection Distance: 8m Max (<24°C)
IP Rating: IP20



IRIS S20 (Occupancy)

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-30min
Load Capacity: 10Amp
Detection Distance: 20m Max (<24°C)
IP Rating: IP20



IRIS F20R (Occupancy)

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-30min
Load Capacity: 10Amp
Detection Distance: 20m Max (<24°C)
IP Rating: IP20



IRIS S6DR

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-30min
Load Capacity: 10Amp
Detection Distance: 6m Max (<24°C)
IP Rating: IP20



IRIS W15

(Wall Mounted - 180° Detection)

Hold Time: 10sec-12min
Load Capacity: 5Amp
Detection Distance: 12m Max (<24°C)
IP Rating: IP65



NEO-E15

(Dual Mode on/off & Waving DC - 12V)

Input: 12-24V / DC
Output: 5Amp
Sensing Distance: 6 to 10cm



NEO-D15

(Dual Mode on/off & Waving DC - 12V)

Input: 12-24V / DC
Output: 5Amp
Sensing Distance: 6 to 10cm



SN-PR123

(Single Door - 230V AC)

Input: 220-240V / AC
Output: 5Amp
Sensing Distance: 6 to 10cm



SN-PC302

Power Source: 220-240V / AC
Rated Current: 10A
IP Rating: IP44
LUX Setting: <5-50 Lux (Adjustable)



GET IN TOUCH

 +91 95867 74775

 +91 99797 64665

 info@sensinova.in

 Sensinova India, C K Patel Estate, Survey
Number 372, Opp. Tata Motors Service
Centre, Near RamaKaka Deri, Chhani,
Vadodara-391740

Scan For More Details



Follow us on:

